

# **DURABAND MICRO UHF SR**



## **FUNCTIONALITY**

RF Protocol: EPC Class 1 Gen 2: ISO 18000-6C

Operating Frequency: UHF - 860 to 960 MHz; Short-range

Memory Configuration: 96-Bit EPC; 32-Bit User Memory; 48-Bit TID

R/W Capability: Read/Write

#### **PERFORMANCE**

Read Range: Up to 8-12"

Quality Guarantee: 100%

Orientation: Front Face Read

IP Rating: IP68

# **PHYSICAL**

Material: PC/PBT Alloy

**Mounting:** Band 0.31" x 0.050" max; 0.125" Dia Wire Rope max

Color: Custom Logo and Colors Available

## **OPERATIONAL**

Max Temperature Exposure:	260°F/ 125°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	260°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

## **DIMENSIONS**

Weight:	1.4g / .05 oz
Dimensions:	0.06" x 0.41"
Thickness:	.34"



## **RECOMMENDED TAG APPLICATIONS**

**Hose:** Hydraulic Hose, Chemical Hose & Pipe

Visit www.infochip.com to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email sales@infochip.com or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

Where is it?

What is it?

Is it safe to use?