

DATABAND2



FUNCTIONALITY

RF Protocol: ISO 15693

Operating Frequency: HF - 13.56 MHz

Memory Configuration: 16 Character UID, 896 bits User Memory

R/W Capability: Read/Write

PERFORMANCE

Read Range: Less than 1"

Quality Guarantee: 100%

Orientation: Front Face Read

IP Rating: IP68

PHYSICAL

Material: PC/PBT Alloy

Mounting System: Metal Band (Pass-through Slot 5/8")

Color: Custom Logo Available

OPERATIONAL

Max Temperature Exposure:	260°F/ 125°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	260°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
IK Impact Rating:	IK10
Water and Ice Proof:	Yes

DIMENSIONS

Weight:	5g / .17 oz
Dimensions:	1.5" x .75"
Thickness:	.38"



RECOMMENDED TAG APPLICATIONS

Hose: Industrial & Chemical Hose, Pipes

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more! For pricing and details, please call 1-816-421-2553.

Holland RFID

(816) 421-2553

https://hollandnameplate.com/holland-rfid/