

**IP Rating:** 



FUNCTIONALITY		
RF Protocol:	EPC Class 1 Gen 2: ISO 18000-6C	
Operating Frequency	UHF - (NA): 902 to 928 MHz (EU): 866 to 868 MHz	
Memory Configuratio	n: 96-Bit EPC; 512-Bit User Memory; 64-Bit TID	
R/W Capability:	Read/Write	
PERFORMANCE		
Read Range:	10ft (results may vary)	
Quality Guarantee:	100%	
Orientation:	Readable in 360° - Range varies with orientation	

**IP68** 

## PHYSICAL

Material:	PC/ PBT Alloy	
Mounting System:	Metal Band (Pass-through Slot 5/8")	
Color:	Custom logo available	

## **OPERATIONAL**

Max Temperature Exposure:	260°F/ 125°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	260°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

## **DIMENSIONS**

Weight:	4.9g / .17 oz
Dimensions:	1.5" x .75"
Thickness:	.25"



**RECOMMENDED TAG APPLICATIONS Hose:** Industrial & Chemical Hose, Pipes

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more! For pricing and details, please call 1-816-421-2553.

## Holland RFID (816) 421-2553 https://hollandnameplate.com/holland-rfid/