

DATABAND MICRO UHF SR



FUNCTIONALITY

RF Protocol: EPC Class 1 Gen 2: ISO 18000-6C

Operating Frequency: UHF - 860 to 960 MHz; Short-range

Memory Configuration: 96-Bit EPC; 32-Bit User Memory; 48-Bit TID

R/W Capability: Read/Write

PERFORMANCE

Read Range:	Up to 8-12"
Quality Guarantee:	100%
Orientation:	Front Face Read
IP Rating:	IP68

PHYSICAL

Material: PC/PBT Alloy

Mounting: Band 0.31" x 0.050" max; 0.125" Dia Wire Rope max

Color: Custom Logo and Colors Available

OPERATIONAL

Max Temperature Exposure:	260°F/ 125°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	260°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

DIMENSIONS

Weight:	1.4g / .05 oz
Dimensions:	0.06" x 0.41"
Thickness:	.34"



RECOMMENDED TAG APPLICATIONS

Hose: Hydraulic Hose, Chemical Hose & Pipe

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more! For pricing and details, please call 1-816-421-2553.

Holland RFID

(816) 421-2553

https://hollandnameplate.com/holland-rfid/