



DURAPLUG6 PPA

(For high temp or pressure see DuraPlug6 PEEK)



FUNCTIONALITY

RF Protocol:	ISO 15693
Operating Frequency:	HF - 13.56 MHz
Memory Configuration:	16 Character UID, 896 bits User Memory
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	Up to 0.1"
Quality Guarantee:	100%
Orientation:	Front Face Read
IP Rating:	IP68

PHYSICAL

Material:	PPA + GF30%
Mounting System:	Metal-embeddable, Press Fit
Color:	Custom Logo and Colors Available

OPERATIONAL

Max Temperature Exposure:	212°F/ 100°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	212°F/ 100°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

DIMENSIONS

Weight:	.17g/ .01 oz
Dimensions:	Diameter 0.236" (6mm)
Thickness:	.089" (2.25mm)



RECOMMENDED TAG APPLICATIONS

Lifting: Shackles, Chain Slings & Other Industrial Equipment

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more!
For pricing and details, please call 1-816-421-2553.

Holland RFID

(816) 421-2553

<https://hollandnameplate.com/holland-rfid/>