



# DURAPLUG8



## FUNCTIONALITY

RF Protocol:	ISO 15693
Operating Frequency:	HF - 13.56 MHz
Memory Configuration:	16 Character UID, 896 bits User Memory
R/W Capability:	Read/Write

## PERFORMANCE

Read Range:	Up to 0.1"
Quality Guarantee:	100%
Orientation:	Front Face Read
IP Rating:	IP68

## PHYSICAL

Material:	PPA + GF30%
Mounting System:	Embeddable * No Adhesive Required*
Color:	Custom Logo and Colors Available

## OPERATIONAL

Max Temperature Exposure:	260°F/ 125°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	260°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

## PRODUCT

Weight:	.27g/ .01 oz
Dimensions:	Diameter 0.315" (8mm)
Thickness:	.128" (3.25mm)



## RECOMMENDED TAG APPLICATIONS

- Oil & Gas:** Downhole Drilling Tools
- Lifting:** Shackles, Hoist Rings, Hooks

Visit [www.hollandnameplate.com](http://www.hollandnameplate.com) to learn about the Holland RFID suite of tags, readers and more!  
For pricing and details, please call 1-816-421-2553.

**Holland RFID**  
(816) 421-2553

<https://hollandnameplate.com/holland-rfid/>