

# PIPETRACKER



#### **FUNCTIONALITY**

**RF Protocol:** EPC Class 1 Gen 2; ISO 18000-6C **Operating Frequency:** UHF - 860 to 960 MHz

**Memory Configuration:** 96 EPC Bits; 512 Bit User Memory

R/W Capability: Read/Write

### **PERFORMANCE**

**Read Range:** Up to 3ft (results may vary)

**Quality Guarantee:** 100%

**Orientation:** Readable in 360° - Range varies with orientation

IP Rating: IP68

#### **PHYSICAL**

Material: Steel

Mounting System: Metal Pipe Cinch

Color: Steel

#### **OPERATIONAL**

Max Temperature Exposure:	300°F/ 150°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	300°F/ 150°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

#### **DIMENSIONS**

Weight:	48g / 1.69 oz
Dimensions:	1.25" x 1"
Thickness:	.41"



#### **RECOMMENDED TAG APPLICATIONS**

Oil & Gas: Surface Pipe

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more! For pricing and details, please call 1-816-421-2553.

## Holland RFID

(816) 421-2553

https://hollandnameplate.com/holland-rfid/