



# PIPE TRACKER 2



## FUNCTIONALITY

<b>RF Protocol:</b>	EPC Class 1 Gen 2; ISO 18000-6C
<b>Operating Frequency:</b>	US: 902 to 928 MHz
<b>Memory Configuration:</b>	96-Bit EPC; 512 User Bit Memory; 64-Bit TID
<b>R/W Capability:</b>	Read/Write

## PERFORMANCE

<b>Read Range:</b>	Up to 6 feet (with handheld reader)
<b>Quality Guarantee:</b>	100%
<b>Orientation:</b>	Readable in 360° - Range varies with orientation
<b>IP Rating:</b>	IP68

## PHYSICAL

<b>Material:</b>	304 Stainless Steel
<b>Mounting System:</b>	Metal Band 0.625" wide MAX

## OPERATIONAL

<b>Max Temperature Exposure:</b>	300°F/ 150°C
<b>Min Temperature Exposure:</b>	-40°F/ -40°C
<b>Continuous Max Service Temperature:</b>	300°F/ 150°C
<b>Continuous Min Service Temperature:</b>	-40°F/ -40°C
<b>Water and Ice Proof:</b>	Yes (Not for continuous immersion)

## DIMENSIONS

<b>Weight:</b>	41g / 1.45 oz
<b>Dimensions:</b>	0.98" x 1.82"
<b>Thickness:</b>	0.33"



## RECOMMENDED TAG APPLICATIONS

**Oil & Gas:** Surface Pipe

Visit [www.hollandnameplate.com](http://www.hollandnameplate.com) to learn about the Holland RFID suite of tags, readers and more!  
For pricing and details, please call 1-816-421-2553.

# Holland RFID

(816) 421-2553

<https://hollandnameplate.com/holland-rfid/>